








268L AQUATECH ALL IN ONE



FEATURES

-  Same footprint as 400L tank
-  350% efficiency, lower running costs
-  WiFi smart controller, hybrid modes
-  Non-sacrificial anode water protection
-  Solar PV integration with timer
-  1800W backup heating element
-  R290 refrigerant, near-zero GWP

5 years labour warranty and
5 years product warranty

SPECIFICATIONS

MODEL	268L
Electricity Supply	220-240 V/50-60 Hz
Circuit	10 Amp/Single Phase
Power Connection	Hardwired/Isolated
Tariff Connection	Continuous/Shoulder/TOU
Compressor Rating	700-900 W
Element Rating	1800 W
Protection Class	IPX4
Refrigerant	R290 (400g)
Sound Rating	42dB(A) @ 1.65m
Tank Material	Vitreous Enamel
Tank Storage Capacity	268L

SPECIFICATIONS

MODEL	225L
Condensate Connection	1/2" Elbow (supplied)
Water Connections	3/4" G
PTR Rating	850 kPa (supplied)
ECV Rating	700 kPa (suggested)
Pressure Reduction Valve	500 kPa (max.)
Tempering Valve	High Performance (suggested)
System Weight	118 kg
System Dimensions	620 mm x 1810 mm
Packed Weight	134kg
Packed Dimensions	700 mm x 1950 mm
Minimum Base Size	600 mm x 600 mm

